

TRIANGLES

LOW CONTENT BRAZED CBN INSERTS - DR-50, 450 & 500

HIGH CONTENT BRAZED CBN INSERTS - DR-75, 85, 95, 400, 650 & 900

PRODUCT RANGE OF DR-CBN CUTTING TOOL INSERTS FOR I.S.O. TOOL HOLDERS - 4mm Edge Length Re-grindable E, F, T or S Edge Condition.



| Product Reference | Inscribed Circle (mm) | Thickness (mm) | Radius (mm)                           | Example Insert |
|-------------------|-----------------------|----------------|---------------------------------------|----------------|
| Triangles         |                       |                |                                       |                |
| TNMA 1604**       | 9.52                  | 4.76           | 0.2 – 1.6                             |                |
| TNMA 1103**       | 6.35                  | 3.18           | 0.2 – 1.2                             |                |
| TNUN 1604**       | 9.52                  | 4.76           | 0.2 – 1.6                             |                |
| TNUN 1603**       | 9.52                  | 3.18           | 0.2 – 1.6                             |                |
| TNUN 1103**       | 6.35                  | 3.18           | 0.2 – 1.2                             |                |
| TCMW 16T3**       | 9.52                  | 3.97           | 0.2 – 1.6                             |                |
| TCMW 1102**       | 6.35                  | 2.38           | 0.2 – 1.2                             |                |
| TCMW 0902**       | 5.56                  | 2.38           | 0.2 – 0.8                             |                |
| TCMW 06T1**       | 3.97                  | 1.97           | 0.2 – 0.4                             |                |
| TPMW 0702**       | 4.20                  | 2.38           | 0.2 – 1.6                             |                |
| TPKN 16T3**       | 9.52                  | 3.97           | 0.2 – 1.6<br>(or milling wiper facet) |                |
| TPUN 2204**       | 12.70                 | 4.76           | 0.2 – 2.0                             |                |
| TPUN 1603**       | 9.52                  | 3.18           | 0.2 – 1.6                             |                |
| TPUN 1103**       | 6.35                  | 3.18           | 0.2 – 1.2                             |                |
| TPKN 1603**       | 9.52                  | 3.18           | 0.2 – 1.6<br>(or milling wiper facet) |                |

Typical Order Example: - 30 pieces VCMW 160404T DR-85