

TRIANGLES



BRAZED PCD INSERTS

PRODUCT RANGE OF DR-PCD CUTTING TOOL INSERTS FOR I.S.O. TOOL HOLDERS - Single Edge Consumable
E, F, T or S Edge Condition, Designated ‘CE’.

Product Reference	Inscribed Circle (mm)	Thickness (mm)	Radius (mm)	Example Insert
Triangles				
TNMA 1604**	9.52	4.76	0.2 – 1.6	
TNMA 1103**	6.35	3.18	0.2 – 1.2	
TNUN 1604**	9.52	4.76	0.2 – 1.6	
TNUN 1603**	9.52	3.18	0.2 – 1.6	
TNUN 1103**	6.35	3.18	0.2 – 1.2	
TCMW 16T3**	9.52	3.97	0.2 – 1.6	
TCMW 1102**	6.35	2.38	0.2 – 1.2	
TCMW 0902**	5.56	2.38	0.2 – 0.8	
TCMW 06T1**	3.97	1.97	0.2 – 0.4	
TPMW 0702**	4.20	2.38	0.2 – 1.6	
TPKN 16T3**	9.52	3.97	0.2 – 1.6 (or milling wiper facet)	
TPUN 2204**	12.70	4.76	0.2 – 2.0	
TPUN 1603**	9.52	3.18	0.2 – 1.6	
TPUN 1103**	6.35	3.18	0.2 – 1.2	
TPKN 1603**	9.52	3.18	0.2 – 1.6 (or milling wiper facet)	

Typical Order Example: - 20 pieces TNMA 120404T CE DR-PCD